

Overview vacuum lifters for the production of insulation glass



The vacuum lifter 7005-MD1/E – MonoPort

1 circuit vacuum lifter

Carrying capacity: max. 150 kg in-company

Manual turning through max. +/- 360°



presentation video



video device in use



The vacuum lifter 7025-MD2/E

1 circuit vacuum lifter

Carrying capacity: max. 250 kg in-company

Pneumatic turning through max. 90°



video device in use



The vacuum lifter 7025-MD4/E

1 circuit vacuum lifter

Carrying capacity: max. 400 kg in-company

Pneumatic turning through max. 90°



The vacuum lifter 7025-MDS4/E

1 circuit vacuum lifter

Carrying capacity: max. 400 kg in-company

Pneumatic turning through max. 90°

Pneumatic tilting through max. 90°



commissioning



photos device in use

The vacuum lifter 7025-MDS8/E

1 circuit vacuum lifter

Carrying capacity: max. 400 kg in-company

Pneumatic turning through max. 90°

Pneumatic tilting through max. 90°

The vacuum lifter 7025-MS4/E

1 circuit vacuum lifter

Carrying capacity: max. 400 kg in-company

Pneumatic turning through max. 90°

The vacuum lifter 7005-AB/E

1 circuit vacuum lifter

Carrying capacity: max. 1250 kg in-company

Device for transporting large, just sealed insulation glass panes without the risk of the glass panes displacing into each other - with support stand



photos device in use

Overview vacuum lifters for the production of insulation glass



The vacuum lifter 7025-BZ-2014/E

1 circuit vacuum lifter

Carrying capacity: max. 1000 kg in-company
special device for transporting
large, just sealed insulation glass panes
without risk of displacing of the glass panes to each
other



commissioning

Insulation glass loading frame 601-ISO4

Carrying capacity: max. 2500 kg in-company
special device for transporting
large, just sealed insulation glass panes
without risk of displacing of the glass panes to each
other



commissioning



photos device in use