


## Accu-Device Kombi 7011-MD1

### MonoPort

for intra-plant use according  
to EN 13155



#### Description

- **1 circuit vacuum system**
- the vacuum circuit has a vacuum tank with nonreturn valve, vacuum switch and control vacuum meter
- **completely closed vacuum circuit**  
prevents loss of vacuum at power failure
- **power failure monitoring system**
- acoustic signal indicates insufficient vacuum
- locking every 90°

#### Vacuum generation

- built-in low maintenance rechargeable battery vacuum pump (dry running system)
- for battery operation with quick-change device for short battery change times of less than one minute
- battery charger for charging second battery
- no cable - no hose

#### Operation

- |           |                               |
|-----------|-------------------------------|
| • ON/OFF  | directly at the device        |
| • SUCTION | hand slide valve              |
| • RELEASE | hand slide valve with locking |
| • UP/DOWN | optionally: via crane switch  |

**Suspension:**  
**Load capacity :**  
**Colour:**

crane eye at the carrying frame  
**150kg**  
silver / partly zinked

<b>suitable for lifting</b>			
material properties	gas-tight		
surface	smooth		
e.g.	glass panes, sealed units, window and curtain walling elements, plastic and ceramic plates, coated boards		
<b>diameter</b> in action approx. mm	400	350	300
<b>quality of suction cups</b>	black rubber abrasion possible heat resistance up to 50°C	rubber red abrasion possible up to 80° C heat resistant from 3 mm glass thickness	black rubber abrasion possible up to 80° C heat resistant from 4 mm glass thickness
<b>safe working load</b> on smooth and clean surface at 60 % vacuum			
<b>in-company</b> kg	150	125	100
<b>dead weight</b> approx. kg			
<b>distribution voltage</b> charger for battery	110 - 230 V / 50/60 Hz / 1 phase		
<b>Item No.: 7011-MD1-...</b>	<b>400</b>	<b>488-K</b>	<b>388</b>

